

FUJI HUNT PHOTOGRAPHIC CHEMICALS, INC.

HEADQUARTERS

40 Boroline Road Allendale, NJ 07401 Tel: 201.995.2200 Fax: 201.995.2299 www.fujihuntusa.com

MANUFACTURING FACILITY

50 Industrial Loop North Orange Park, FL 32073 Tel: 904.264.3500 Fax: 904.278.9697 www.anchorlith.com





THE FUNCTION OF FOUNTAIN SOLUTION IN LITHOGRAPHY





INTRODUCTION

We all view lithography as such an everyday phenomenon that perhaps you have not carefully thought about the role that water/fountain solution plays.

You might say that the answer is obvious, "Keep ink off the background areas while the press is printing and protect the plate when the press stops."

We'll respond with, "You are correct, but that is far from the complete story." Lithography is a complicated and often mysterious process, at least whenever it's not working well. This process is both physical and chemical in nature which means that a lot is going on. Later you will grasp both the chemical and physical aspects in greater detail.

We hope that you find this book to be interesting and helpful in your daily work. If you have any questions or comments, please feel free to call or write to us at:

Technical Staff Fuji Hunt Photographic Chemicals, Inc. 50 Industrial Loop North Orange Park, Florida 32073 800.354.2300 or 904.264.3500 www.fujihuntusa.com | www.anchorlith.com

CONTENTS

The Functions	
Supply a Film of Water	2
Desensitize the Background	2
Cleaning	3
Rapid Spreading and Dampening Throughput	3
Lubrication	5
Emulsification Control	5
Summary	6
The Chemistry	
Introduction	7
Ingredients	7
Desensitizing the Background	8
Cleaning the Background During Press Starts	9
Water Leveling	10
Water Flow	
A Uniform Film	11
Dynamic Surface Tension	12
Water Throughput	
Alcohol	14
	17
LUDRICATION	16
Piling and Linting	
Piling	17
Linting	18
Emulsification	
Emulsification of Fountain Solution into Ink	19
Summer only	20
Summary	20

Printed in USA 2/03.

Copyright © 1993-2003. All rights reserved. No portion of this booklet may be used or reproduced in whole or part without our written consent.

1

THE FUNCTIONS

Let's begin with two simple observations; turn down the water and ink starts to print in the non-image, turn up the water and the ink starts to leave the image. You are seeing competition of both ink and water for image and background. When the process is working well it is said that the ink and water are in balance. Each surface is carrying a thin film of primarily the intended material. Notice that even though the two surfaces are very different, both can accept ink or water.

Supply a Film of Water

If the plate is allowed to run too dry, ink will begin to wet the background and print and you will have what is called scumming. This occurs because there is not enough water to coat the plate surface completely, and the bare aluminum accepts ink.

Thus, function number one is to provide an adequate film of water.

Desensitize the Background

There are important differences between the image and background surfaces which explain the physical process that makes lithography work.



Here you see two water drops. On the left the water spreads across the water-loving (Hydrophilic) background while on the Hydrophobic (water-hating) image, the water beads.

THE FUNCTIONS

Think of the background as pulling out on its water drop, causing it to spread into a thin layer. The background surface is literally pulling outward with a kind of capillary action.

It is critical for fountain solution to maintain this hydrophilic surface of the background. However, the image is similar to a freshly waxed car. The water does not "wet" the paint (or image in this case) but only beads up, and the fountain solution must not convert the image to a hydrophilic nature (we call this blinding of the plate).

Cleaning

The next example is not quite so simple. Ink up a dry plate, and we see that the ink sticks well everywhere; it "wets" both the image and the background. If it's a good plate and you gently rub the background with a wet pad, the ink will lift off and be displaced by water. The same capillary forces that caused the water to spread to a thin film will draw the water under the ink and "float" it off. If we had used fountain solution rather than plain water, the surface would be "cleaned" more efficiently. This cleaning process is critical during press starts.

Rapid Spreading and Dampening Throughput

The fourth and fifth functions promote the water spreading on the background and rollers; fountain solution helps the water flow evenly and smoothly through the dampening rollers onto the plate. It is critical to achieve a thin, uniform film of water across the plate surface. This must happen quickly—in the time that the plate cylinder rotates from the dampening form roller to the blanket. On modern high-speed web presses, this time is very short (0.05 seconds at 1500 fpm).

THE FUNCTIONS

The dampening rollers always impart nonuniformities similar to the ridges that a paint brush leaves before the paint has had a chance to "flow" out. This same "flowing out" must occur on the plate surface.

Additives are used to promote this rapid spreading and flow across the plate surface. They are called wetting agents or surface active agents (surfactants). These materials, when dissolved in your fountain solution, reduce the surface tension of the water. Look at how they work.

A vector diagram from physics makes this easy to understand. When a water drop is sitting on a surface there are two important forces (represented by the arrows) acting on the water.



Force 1 - Surface Energy of the Plate Pulls Out Force 2 - Surface Tension of the Water Pulls In

The balance of these two forces determines how easily the drop spreads. Fountain solution has a dual role affecting both forces. The surfactants (wetting agents) reduce the surface tension thus making the inward forces smaller. The desensitizers maintain the hydrophilic surface, thus increasing the outward forces. The net result is that fountain solution, when it's working well, promotes good spreading by increasing the outward forces and minimizing the inward forces.

THE FUNCTIONS



On the left, observe the proper balance of forces; while on the right, the fountain solution is trying to bead up on the plate background. This plate may tend to be sensitive to ink.

Lubrication

The sixth function is lubrication and anti-piling. Fountain con-centrates should contain lubricants and "release" agents for the blanket. The film of water carried on the plate background retards friction wear, thus increasing plate life. This reduction of friction prevents the ink train and plate surface from over heating. It has been shown that paper lint and dried ink resin do build up on the blanket, and this is called piling or linting. The release agents help to prevent the blanket from becoming "sticky" thereby picking excessive paper linters.

Emulsification Control

The final function is to help prevent excessive emulsification of water into the ink (formation of a water-in-oil emulsion). The ink maker designs his ink to print correctly after it has taken on some water. This "emulsified" water is essential to proper ink transfer and required to maintain open reverses.

It is also critical to not promote the formation of oil-in-water emulsions. This "oil-in-water" condition is what happens when the detergent in your washer takes oily soil off the clothing. The fountain solution must not break down the ink or it will pass into the water. If tiny ink or pigment particles are floating around in the water they can stain the background or print as a light tone.

THE FUNCTIONS

Summary

The seven functions can be summarized as follows:

- 1. Keep ink off the background with a film of water.
- 2. Maintain the hydrophilic nature of the background.
- 3. Quickly clean ink off the background during press starts.
- 4. Promote fast spreading of water over the plate surface.
- 5. Help the water flow evenly through the dampening rollers.
- 6. Lubricate the plate and blanket.
- 7. Control emulsification of ink and water.

You can now imagine that to accomplish these tasks is much more complicated than just providing water to the background of the plate. In rare instances, water might work; but most printers would find it difficult to work with.

In the next sections you'll examine what chemicals are used and see in greater detail how fountain solution actually works.

THE CHEMISTRY

Introduction

The fountain solution's assignments have been listed. By studying the chemistry and physics of fountain solution, you will better understand how the tasks are accomplished.

Most American fountain solutions are formulated in a somewhat similar manner; however, this is not to imply that they all perform equally well. There are many ways to accomplish the functions and some of these are much more efficient than others. The following are the major classes of ingredients used in fountain solutions:

Ingredients

- Water soluble gums.
- A pH buffer system.
- Desensitizing salts.
- Acids or their salts.
- Wetting agents (also called surfactants).
- Solvents.
- Non-piling or lubricating additives.
- Emulsion control agents.
- Viscosity builders.
- Biocides (fungus, bacteria, and mold control agents).
- Defoamers.
- Dyes.

THE CHEMISTRY

Desensitizing the Background

Recall the discussion of the hydrophilic nature of the background. When the plates are manufactured, the aluminum surface is treated to be both durable and water-loving. As the plate wears and is constantly exposed to ink and dirt, this treatment must be renewed. Several ingredients contribute to this renewable desensitizing:

Water soluble, film-forming gums—gum arabic has been the choice of lithographers for many years. This is the dried sap of the acacia tree that grows in parts of Africa. This gum is very water soluble and has a high affinity for aluminum metal. It bonds best at pHs near four. Other water soluble polymers such as larch gum, starches, CMC, PVP, some acrylics and others have also found use as plate desensitizers. After each application of fountain solution, a small amount of gum adheres to the background providing a protective film. When the press is stopped for any length of time, it is very important that this gum film is adequate to protect the plate from oxidation or handling.

Desensitizing salts—several inorganic salts aggressively react with aluminum metal to form hydrophilic compounds. These salts all contain what are called strong polar bonds which attract water (hydrophilic, again). Examples are silicates (Si-O4) and phosphates (P-O4). Notice that both contain oxygen atoms (O); these polar oxygens will stick up from the plate surface and draw water.



THE CHEMISTRY

Plates are often treated during manufacturing with these same salts following the anodizing to impart a durable, corrosion-resistant surface.

Cleaners—in a secondary role are acids, solvents and wetting agents. These act as cleaners and tend to remove any accumulated oily soil from the plate surface. If left to build up, this soil will attract ink and cause sensitivity. Acids, like phosphoric, are used for metal cleaning to "brighten" the surface. This is where the term "etch" came from. A very thin layer of metal, only a few molecules thick, is dissolved off the plate exposing a fresh surface.

Cleaning the Background During Press Starts

Commonly, ink will get on the dry background when the press stops. Recall that ink will easily "wet" the non-image if it is dry. When the dampeners come back on, it's essential that the fountain solution displace this ink quickly. Minimizing waste is the name of this game! If conditions are right, the ink will almost instantly return to the ink forms, and the first sheet will then be clean. If the ink passes into the fountain circulator and forms an "oil-in-water" emulsion, the suspended ink can cause toning problems.

The sequence of events during a press shutdown and restart goes something like this:

- 1. The thin film of fountain solution dries on the plate.
- 2. Ink may get on the background after shutdown if the press is inched.
- 3. During restart, fountain solution is applied to the water form roller wetting the background.
- 4. The dried gum film should dissolve and lift off any ink or dirt.

THE CHEMISTRY

5. The desensitizing ingredients will reestablish the hydrophilic layer on the background, and the plate will be printing clean.

A failure at any point will slow the restart and cause more spoilage. To sum up restarts:

- There must be a thick enough film of gum from the evaporating fountain solution.
- The gum film must be readily soluble when the water returns.
- · The wetting agents should help remove any oily soil.
- The desensitizing salts must reestablish the hydrophilic surface which will strongly attract water.

Water Leveling

Printing is a very dynamic process, especially on newer highspeed web presses. Conditions at the important printing nips are very different from a beaker sitting in the laboratory. This is the main reason that so-called "models" of press conditions often fail to duplicate working results. An example of this was the "first generation" alcohol substitutes that looked promising in the lab but worked very poorly on press. Their designers failed to consider the dynamic requirements.

The dampening assignment is deceptively simple; rapidly lay down a thin, uniform film of water across the plate surface. Press engineers have worked hard to mechanically improve over the original conventional ductor design of the dampening train. They have tried sleeves, sprays, brushes, slip nips, oscillators, etc. to help provide a more uniform water film.

WATER FLOW

A Uniform Film

Two requirements must be met to obtain a uniform film:

- 1. At the instant the water form roller and the plate split, the ratio of wettest to driest areas must be a minimum across the plate.
- 2. Any surfactant in the fountain solution or alcohol substitute must be capable of acting very quickly to allow for the maximum leveling that is possible.



This plate is going to be very tricky to run, because the dampening system has laid down a film of widely varying thickness. This film will never be able to flow out in time.

This plate, however, has taken a fairly even charge of water and will be easy to run.

The plate must be dampened sufficiently to prevent scumming in the driest area. If the film is uniform, the overall amount of water reaching the plate will be a minimum; and ink/water balance will be easiest to obtain.

WATER FLOW

Dynamic Surface Tension

Any surfactants that are in the fountain solution must be capable of acting very quickly. This is called good "Dynamic Surface Tension Reduction." When a water film is split (at the nips, for example) these surfactant molecules react by traveling (migrating) to a water surface. To be effective, the molecules must line up with their hydrophilic ends pointed towards the surface. They have no effect while inside the body of the liquid.



Observe on the left how the molecules have lined up quickly with their hydrophilic ends pointed to the fresh surface. On the right most of the molecules are still floating around randomly, and there will be little surface tension reduction of this film, because the molecules were too slow to reach the new surface.

WATER FLOW

Dynamic Surface Tension

-continued

The strength and concentration of the surfactant controls how much the surface tension will be reduced, but of greater importance the "migration speed of the molecules" controls how quickly the reduction or rapid wetting will occur on press.



Observe how both solutions reach a surface tension of 30, but that in the first graph (Surfactant II) it takes so long that at faster press speeds this will not be effective. Surfactant I is effective after only 0.05 seconds and will work well at highest speeds.

WATER THROUGHPUT

The other important aspect of dampening flow is what we call "Water Throughput." This term describes how easily the fountain solution will move from the water pan through the dampening train and finally onto the plate. This is of primary importance with the continuous flow/alcohol type dampening systems. Alcohol's main function is to promote higher "throughput" and level water films. Both surfactants and viscosity builders in fountain concentrates will increase water flow and thus imitate the performance of alcohol.

Increasing the **viscosity** implies making the solution "thicker" and that seems contrary to the common sense notion of "making the water wetter or thinner" so that it will pass the metering nip more easily. However, as the viscosity increases, the water film at the rubber roller surface will be dragged through the nip more effectively. Think of it as trying to wipe off a film of 90 weight gear oil versus paint thinner.

Alcohol

Let's briefly examine alcohol and why it is used so frequently. Common sense tells you that alcohol makes the "water wetter" and improves dampening flow. The following facts will help to explain why alcohol is so popular and seems to solve a myriad of press problems:

- Alcohol is a weak wetting agent.
- Alcohol evaporates from the ink train quickly, leaving no residue.
- The evaporation helps cool the ink train.
- The viscosity of water increases as IPA is added (up to about 25% alcohol concentration by volume).
- Alcohol is used at high percentages compared to other fountain ingredients.

WATER THROUGHPUT



Alcohol gives only medium surface tension, but, because the molecules are small, it's dynamic properties are exceptionally good. Recall the migration diagram—there are 100 to 200 times as many alcohol molecules near a fresh surface than the surfactant molecules in an alcohol substitute. What this means is that alcohol, because of its high use level, will give very fast surface tension reduction. Successful alcohol substitutes mimic the surface and viscosity behavior of alcohol closely.



LUBRICATION

Running a thin film of fountain solution over the plate surface, blankets, and rollers prevents excess friction, heat, and wear. Several additives such as alcohol substitutes, polymers, and glycols are used in fountain solutions to enhance the lubricating effect of water.

Without adequate lubrication between the plates and the form rollers there would be tremendous friction and rapid plate wear. We must also prevent the blankets from becoming too tacky (sticky) thus pulling off paper fibers, which is known as **picking**.

Recall the **water-in-oil** emulsion formed when the dry ink picks up fountain solution. As the plate passes under the forms some water is squeezed back out of the ink providing a cushioning effect between the roller and the plate. If the forms are not turning at exactly plate speed (which they usually won't be), the ink/water cushion provides slip preventing friction wear.



The rollers are covered by a film of *both* ink and water. This provides the vital slip needed to prevent wear.

PILING AND LINTING

Piling

One definition of **piling** is—a build up of ink (or ink components) and paper linters, generally on the blanket. This is a major concern for web printers because of the waste generated each time that the blankets must be cleaned. As these materials build and the blanket thickness increases in local areas, print quality will deteriorate. You will generally see this build up in the non-image area of the blanket, and it tends to be worst at the trailing edge of solids.



When the piling becomes thicker, the trailing edge of the image will begin to lift off the blanket and stop printing. Piling is a very good indicator of fountain solution, ink, and paper compatibility. On good stock, the blankets may only require cleaning

every 200,000 impressions. The image does not usually pile, because fresh ink is constantly being transferred from plate to blanket to paper. This constant transfer tends to prevent any significant accumulation of foreign material on the blanket.

There are several contributing factors that influence the rate of piling:

- 1. The amount of water being carried on the plate/blanket. Running too dry generally increases the rate of piling.
- 2. The "speed" of the inks. Inks formulated with faster oils may tend to dry out and pile rapidly.
- 3. The lubricating ability of the fountain solution.
- 4. The type of plate used (smooth grain plates usually pile less).
- 5. Paper surface—loose fiber may be pulled off and added to the accumulated ink resin.

PILING AND LINTING

Linting

Linting is caused by stock with loose surface fibers or by excessive tack of the ink or blanket. Paper fibers are pulled off the sheet and then build up on the blanket. "Release Agents" are often included in fountain solutions or alcohol substitutes to decrease the "tackiness" of the blanket surface and reduce the tendency to pull the fibers off the sheet. Typical non-piling additives are made from glycols that will tend to keep the blanket moist.

Some printers will run paper that has loose surface fibers through a dummy unit before laying down the first color. Some of the loose surface fibers will be pulled off and stick on the dummy blanket reducing linting in subsequent units.

EMULSIFICATION

Emulsification of Fountain Solution into Ink

Ink must take on water to work correctly. This statement may seem contrary to intuitive thinking; however, the water film that is always covering the ink on the rollers must have some place to go. Part of the water passes into the ink, improving the flow and transfer characteristics. Of concern is *how much* water and exactly *how is the water distributed* while in the ink. The term **Emulsion** means a two phase system of liquids that do not chemically combine or dissolve into each other. If you looked at the ink on the forms under a microscope, you would see droplets of water suspended in the ink.



Ink I. will print smoothly with a fine grain structure. Ink II. will be snow-flaky or print with an "orange peel" look. Whenever ink is squeezed at the printing nips, these large (loosely held) water droplets will come back out of the ink and show up as voids in the image.

If the ink is too dry (low water pickup) or the water too tightly held, there will be problems with scumming or filling in of reverses. The water to keep the reverses or trailing edges of solids desensitized must come from the ink. Picture the water being compressed into the ink during the form roller squeeze and then popping back out after the image has passed the form roller.

The fountain solution should *not encourage* the ink to emulsify into the water phase.

19

SUMMARY

We hope that you now have a better understanding of some of the chemical and physical aspects of the dampening process. Many man-years of research and development have gone into improving inks and fountain solutions. There are still no "ideal" combinations of products or equipment, because water and ink are both antagonists and partners in the lithographic process.

Think in terms of a "whole system" or "window of effective operation" as printers and suppliers our joint assignment is to increase the latitude or "window" of the process. Combinations with wide latitude are easier to use and will yield consistently superior results.

A better understanding of dampening chemistry will help you diagnose and then correct any problems that occur from time to time. Carefully controlling and monitoring your dampening chemistry will prevent problems caused by *"over or under use"* and will provide important data in the event of trouble.

Finally, encourage your suppliers to work together to help you obtain that "optimum" system to match your needs.